

97300T Waste Gas Burner with Touch Screen Control Panel

Designed for complete automatic operation of the entire Flare System, The S&J 97300T Waste Gas Burner and Touch Screen Control Box are designed to combust biogases generated in fermentation processes. It efficiently incinerates low BTU gases from anaerobic digesters, lagoons, and municipal landfills, minimizing odors and VOC's. The stoichiometric pilot ensures that a proper air to fuel mixture is maintained throughout the wide range of pressure and BTU fluctuations. A continuous burning pilot in the flame area provides stable, controlled, nonsmoking, combustion.

The 97300T is designed to withstand wind speeds up to 150mph as well as seismic zone 4 loads. Its stainless steel components endure the severest of process environments. The burner tip is designed with swirl inducers that create a cyclonic effect producing an efficient air/fuel mixture and maximizes flame retention. The wind shroud induces sufficient air to the flare tip for proper mixing and combustion throughout the operating range.

Paired with a touch screen control box, the flare is designed for automatic operation and gives the operator more flexibility in controlling the system. The Control Box can also be connected to a local PLC.

The Pilot Control Box utilizes state of the art electronics and instrumentation for safe operation. Pilot controls are enclosed in a NEMA 4, carbon steel, electrical enclosure (NEMA 4X, 304 or 316 optional). For automatic operation, the flare's pilot can be designed to operate only during initial startup or continuously. The Pilot Control Box includes a dry contact input for Remote Start from a SCADA system or a pressure switch. It also includes Contact Status outputs for Alarm and Flame Proven.

The auto-ignition sequence is started by the closing of the remote start contact or pressure switch contact. This will indicate that the gas pressure limit has been reached and flaring of excess gas should begin. The operation of the burner will continue until the contact opens.



Features

- High Performance Stoichiometric Pilot
- No Flame Front Burn-out of Pilot Gas During Ignition
- Sizes 2" Through 12"
- Touch Screen Control Panel
- Burns High Flow, Low BTU "Wet" Methane
- No Venturi Maintenance
- State-of-the-Art Digital Control
- Fully Automated Pilot: Continuous or Intermittent While Flaring
- Provides Alarm Outputs

Specifications:

Sizes:

2", 3", 4", 6", 8", 10" & 12"

Stack Burner Connection:

ANSI 150 lb. Raised Face Flange

Contact Outputs:

Alarm SPST, 120 VAC 1 Amp
Flame Proven SPST, 120 VAC 1 Amp
Other Status Outputs Available

Power Requirements:

120 VAC 4 Amp, 240 VAC 2 Amp (Optional)

Controller:

Temperature Range: -20 to 150 degrees F
Enclosure: Steel; NEMA 4X,
Stainless Steel
Functions: Manual Start, Remote Start
Automatic Sequencing
Continuous Pilot or
Intermittent Pilot

Stack Materials:

Stack with Shroud: 304L Stainless Steel
316L Stainless Steel (Optional)
Piping: 304L Stainless Steel
316L Stainless Steel (Optional)

Biogas Criteria Composition:

50%-70% CH₄, 50%-30% CO₂, with trace amounts of
H₂S, Inert Gases and Air

Moisture Content:

Saturated (100% Humidity)

Pilot Gas:

Natural Gas
Propane (LPG)
Waste Gas (500 BTU/ Cubic Foot Minimum)

Pilot Gas Pressure:

12" W.C. - 10 PSIG

Functions:

Manual Start:

The operator puts selector to manual and initiates ignition by depressing start on the touch screen control panel.

Remote Start:

Remote ignition is performed by placing selector switch in the auto position and closing the remote location dry contact to initiate the operation of the waste gas burner.


Auto Start:

Automatic Start is performed by the sensing of a pressure permissive in the system. The pilot control panel must be set to "Auto" position for this to be controlled by the pressure switch. When the pressure switch contacts close, the auto flaring sequence will begin. Once the pressure drops below the pressure switch set point the contacts will open, halting operation.

Accessories:

A back pressure regulator / deflagration arrester should be installed in the digester line just upstream of the flare. For automatic operation, the solenoid option must be selected on the back pressure regulator.

Dimensions:



Stack Dimensions

Size	Dimensions (Inches [mm])		
	A	B	C
2 [50]	16 [406]	24 [610]	88 [2235]
3 [75]	18 [457]	24 [610]	92 [2337]
4 [100]	20 [508]	24 [610]	92 [2337]
6 [150]	24 [610]	36 [914]	128 [3251]
8 [200]	24 [610]	48 [1219]	144 [3658]
10 [250]	30 [762]	48 [1219]	176 [4470]
12 [300]	36 [914]	60 [1524]	188 [4775]

Flow specified for gas with 0.8 specific gravity, air at 60° F, and .5" WC pressure drop

Capacity

Size (Inches mm)	Capacity (FT ³ /Hr.)
2 [50]	4000
3 [75]	9970
4 [100]	19150
6 [150]	44200
8 [200]	76800
10 [250]	129000
12 [300]	218600

97300T Ordering Guide

Model Number Selection

The model number will have a base number **97300T** followed by 8 digit numbers. These digits will represent 8 sets of option tables.

97300T - AB - CD - EF - GH

Table A - Pilot Gas

Option A	Pilot Gas
0	Natural
1	Propane
2	Bio
3	Dual

Table B - Unit Size

Option B	Unit Size
2	2"
3	3"
4	4"
5	6"
7	8"
8	10"
9	12"

Table C - Power / P.E. Certificate

Option C	Description
1	120 VAC, 60HZ
2	220/240 VAC, 50/60HZ
3	120 VAC, 60HZ with P.E.
4	220/240 VAC, 50/60HZ with P.E.

Table D - Enclosure Rating / UL

Option D	Description
0	NEMA 4X - Carbon Steel
2	NEMA 4X - 304 Stainless Steel
3	NEMA 4X - 316 Stainless Steel
4	NEMA 4X - Carbon Steel (UL 508A)
6	NEMA 4X - 304 SS (UL 508A)
7	NEMA 4X - 316 SS (UL 508A)

Table E - Control Inputs

Option E	Description
1	1 Dry Contact Input
5	2 Dry Contact Inputs
6	1 4-20MA Analog Input
7	1 4-20MA Analog + 1 Dry Contact Input

Typically Dry Contacts are used for SCADA or pressure switch. Analog for pressure transmitter.

Table F - Pilot Type

Option F	Description
1	Continuous (ON while flaring)
2	Intermittent (OFF while flaring)

Table G - Gas Train

Option G	Description
0	Standard*

* Standard regulator pressure is 10 PSIG max

Table H - Materials of Construction

Option H	Stack / Piping
2	304(L) Stainless Steel / 304(L) Stainless Steel
4	316(L) Stainless Steel / 316(L) Stainless Steel
5	304(L) Stainless Steel / 316(L) Stainless Steel
6	316(L) Stainless Steel / 304(L) Stainless Steel

NOTE: Pilot Material 316 Stainless Steel

Accessories

PART NUMBER	DESCRIPTION
9730-10124	Pressure Switch - Explosion Proof, 30" W.C. Adjustable Deadband 1/4" NPT
122200	Pressure Transmitter - Explosion Proof, 1/2" NPT, 4-20 Output, 1.5 PSI Max

L&J Technologies or any of its subsidiaries assume no responsibility and shall not be liable for any damage, injury or death caused by the mis-application or improper installation of the products that it provides. Installation shall be per manufacturer's instructions in accordance to any applicable local, state or federal regulations. It is the responsibility of the purchaser to ensure these guidelines are followed and that the products are applied properly.