

MCG 2150 Remote Calibrator

With the MCG 2150 Remote Calibrator, setup, programming and calibration become a matter of "remote control." When used with any of the L&J gauging products (with Infrared Pickup), this compact intrinsically safe wireless unit allows the operator to access, view, and change programming data without ever removing the explosion proof housing. It is simply a matter of standing within ten (10) feet of the readout and pressing the entry keypad.

This battery powered unit requires no physical coupling to the gauge. In addition, the MCG 2150 Handheld Calibrator is UL and ATEX/CENELEC approved for intrinsically safe operation.



Applications

Troubleshooting	Field Calibration
Field Programming	ATEX/Cenelec Approved
UL Approved	ABS Approved

Features

- Field Calibration without Wires
- Field programming without Wires
- Reduced Start-Up Time
- Ideal for Explosive Environments

MCG 2150 Ordering Guide

MCG 2150 Remote Calibrator

(MCG 2150 is an Intrinsically Safe Device)

The MCG 2150 Remote Calibrator communicates with the following:**

MCG 1200M - Analog/Digital Transmitter	MCG 1800 - Radar Level Gauge
MCG 1350M - Ground Level Display	MCG 2000MAX - Transmitter
MCG 1500SFI - Servo Gauge	evo 2600 - Radar Gauge
MCG 1600SFI - Radar Level Gauge	

**The gauges or transmitters must be ordered separately, works with all L&J Infrared devices

Model Number Selection:

The model number will consist of a base number **MCG 2150** followed by a digit. These digits will represent 1 option table:

MCG 2150 - A

A - Approval Rating	
U	UL - Class I, Groups C & D
B	CENELEC/ATEX II 1 G, EEX [ia] IIC T5

All designs subject to change. Certified dimensions and specifications available upon request.